

3262i / 4062i

## Rapid input. Secure output.

New requirements call for new ways of thinking. With this in mind, we have produced our 3262i and 4062i A3 b/w multifunctional systems to respond to your users future needs. Starting at an output speed of 32 or 40 pages per minute, a high resolution of 1,200 x 1,200 dpi for top-quality prints and a wide array of finishing options and original feeders.

Whether it's the external finisher\* which can staple up to 65 sheets, or the multi-tray with seven trays for filing individual print jobs, these options, plus many more, are available with the 3262i and 4062i. Both systems were developed and optimised with a view to meeting current environmental requirements.

### What you can expect :



**Extraordinary performance :** Both systems work with a high resolution of 1,200 x 1,200 dpi for top-quality prints. The large colour touch display (22.86 cm in size) can be used and adjusted intuitively. Up to 58 function icons can be configured individually. This means that the user can immediately copy or send at the touch of a button and also have faster access to saved print data in the user and print job boxes.



**Fantastic flexibility :** Choose between three different optional feeders. The main highlight is the dual scanner, which can read a maximum of 160 image pages in one minute. The manual feeder linked to up to five feed sources\* facilitates the processing of different types of media, paper formats and paper weights, which can also be output via the default job separator.



**Smart networking and security :** Alongside software solutions\* such as follow-me printing that can be integrated via the HyPAS interface, NFC (Near Field Communication) transmission technology offers enhanced flexibility and increased security. Print jobs can be confirmed and printed via smartphone or tablet authentication with the system. As data transfer is carried out over a short distance, the possibility of unauthorised parties reading your data is minimised. The Data Security Kit\* guarantees additional security.



**Environmentally friendly technology :** Environmental awareness is at the forefront of the 3262i and 4062i multifunctional systems. Both systems were developed and optimised with a view to meeting current environmental requirements in terms of energy efficiency and environmental friendliness. Functions such as duplex printing and automatic skipping for blank pages reinforce this line of thinking, as resources such as paper, toner and time are saved in your everyday workflows.



\* optional

3262i / 4062i  
Digital multifunctional system  
Copy / Print / Scan / Fax  
A3

# 3262i / 4062i

## Technical Data

### General

|                              |  |
|------------------------------|--|
| <b>Type</b>                  | Desktop  |
| <b>Function</b>              | Copy, print, scan, optional: fax   |
| <b>Print technology</b>      | Laser b/w  |
| <b>Original format</b>       | max. A3 via la vitre d'exposition  |
| <b>Copy/print speed</b>      | 3262i : max. 32 pages A4/min.<br>et max. 17 pages A3/min.,<br>4062i : max. 40 pages A4/min.<br>et max. 21 pages A3/min.  |
| <b>1st page (Copy/Print)</b> | 4,3/4,9 seconds* (3262i),<br>3,6/4,2 seconds* (4062i)  |
| <b>Warm-up time</b>          | 18 seconds*  |
| <b>Copy resolution</b>       | 600 x 600 dpi  |
| <b>Greyscales</b>            | 256  |
| <b>Paper feed</b>            | 2 x 500 sheet universal cassettes (A5R-A3),<br>100 sheet multi-bypass (A6R-A3)   |
| <b>Paper weights</b>         | Universal cassette 60-163 g/m <sup>2</sup> ,<br>multi-bypass 45-256 g/m <sup>2</sup> ,<br>duplex 60-160 g/m <sup>2</sup> |
| <b>Paper output</b>          | 250 sheet A4   |
| <b>Job Separator</b>         | Standard, 50 sheet   |
| <b>System memory</b>         | 2 GB RAM, 32 GB SSD**/ optional: 320 GB<br>HDD** (3262i)<br>2 GB RAM, 8 GB SSD**, 320 GB HDD**<br>(4062i)                |
| <b>Continuous copying</b>    | 1-999 copies   |
| <b>Zoom</b>                  | 25 %-400 % in steps of 1 %   |
| <b>Functions</b>             | Touch screen, duplex, 1,000 management<br>codes, skip blank pages etc.   |

### Dimensions/Weight

|                   |                                |
|-------------------|--------------------------------|
| <b>Dimensions</b> | 683 x 594 x 696 mm (H x W x D) |
| <b>Weight</b>     | approx. 59 kg                  |

### Environment

|                          |   |
|--------------------------|---|
| <b>Mains voltage</b>     | 220/240 V, 50/60 Hz   |
| <b>Power consumption</b> | approx. 1,620 W max, approx. 510 W<br>(3262i)/600 W (4062i) in operation, approx.<br>100 W in stand-by mode, approx. 1 W in<br>sleep mode, TEC value: 1.4/1.9 KWh/week<br>(3262i/4062i) |
| <b>Safety</b>            | GS/TÜV, CE  |

### Print System

|                     |                              |
|---------------------|------------------------------|
| <b>Type</b>         | Integrated within the system |
| <b>Print format</b> | A6R-A3                       |

### Print System

|                          |   |
|--------------------------|---|
| <b>Print resolution</b>  | 1 200 x 1 200 dpi, 9 600 x 600 dpi level  |
| <b>Processor</b>         | Freescale QorIQ T1024 (Dual Core) 1,0 GHz   |
| <b>Interfaces</b>        | USB 2.0, 10/100/1000BaseTX, hôte USB,<br>NFC  |
| <b>Network protocols</b> | TCP/IP, Net BEUI  |
| <b>Operating systems</b> | Windows 7/8.1/10; Windows Server<br>2008/2008 R2/2012/2012 R2/2016, Novell<br>NetWare***, Linux, Mac OS 10.8  |
| <b>Emulations</b>        | PCL6 (5e, XL), KPDL 3 (compatible<br>PostScript 3), XPS, PDF 1.7, PRESCRIBE lie   |
| <b>Functions</b>         | impression depuis clé USB, impression<br>directe de PDF/XPS, impression e-mail,<br>impression sécurisée, impression des<br>codes barre, Mobile Print (Android/iOS)/<br>Apple AirPrint, Google Cloud Print |

### Scan system

|                          |  |
|--------------------------|--|
| <b>Scan type</b>         | CCD colour and b/w   |
| <b>Scan format</b>       | max. A3  |
| <b>Scan speed</b>        | max 80 (simplex) or 160 (duplex) A4<br>originals/min in colour and b/w with<br>DP-7110 (300 dpi)             |
| <b>Scan resolution</b>   | 200 dpi, 300 dpi, 400 dpi, 600 dpi   |
| <b>Scan mode</b>         | Photo, text, photo/text, optimised for OCR   |
| <b>File types</b>        | TIFF, PDF, PDF/A, high compression PDF,<br>encrypted PDF, JPEG, XPS, Open XPS                                |
| <b>Interface</b>         | 10/100/1000BaseTX  |
| <b>Network protocol</b>  | TCP/IP   |
| <b>Operating systems</b> | Windows 7/8.1/10; Windows Server<br>2008/2008 R2/2012/2012 R2/2016   |
| <b>Functions</b>         | Scan to SMB, scan to e-mail, scan to FTP,<br>scan to USB, TWAIN scan, WIA scan, SMTP<br>authentication, LDAP |

### Optional fax system 12

|                           |                              |
|---------------------------|------------------------------|
| <b>Compatibility</b>      | Super G3                     |
| <b>Original format</b>    | max. A3                      |
| <b>Modem speed</b>        | 33,6 kbps                    |
| <b>Transmission speed</b> | 3 seconds or less using JBIG |
| <b>Compression method</b> | JBIG, MMR, MR, MH            |

### Optional fax system 12

|                          |  |
|--------------------------|--|
| <b>Fax resolution</b>    | Standard (200 x 100 dpi), fine (200 x 200<br>dpi), super fine (200 x 400 dpi), ultra fine<br>(400 x 400 dpi), 600 x 600 dpi  |
| <b>Fax memory</b>        | 170 Mo   |
| <b>Abbreviated dial</b>  | 2 000 numéros  |
| <b>One touch dial</b>    | 1 000 numéros  |
| <b>Group dial</b>        | 500 numéros  |
| <b>Operating systems</b> | Windows 7/8.1/10; Windows Server<br>2008/2008 R2/2012/2012 R2/2016   |
| <b>Functions</b>         | Pilote de télécopieur réseau, recombinaison<br>automatique du dernier numéro, envoi<br>décalé, max. 2 options télécopieur pour la<br>transmission et la réception simultanées<br>des fax |

### Options

|                        |   |
|------------------------|---|
| <b>Original feeder</b> | DP-7100 document processor with auto-<br>matic reverse function (A6R-A3, capacity:<br>140 sheet A4, paper weight 35-160 g/m <sup>2</sup> ),<br>DP-7120 document processor with auto-<br>matic reverse function (A5R-A3, capacity:<br>50 sheet A4, paper weight 45-160 g/m <sup>2</sup> ),<br>DP-7110 document processor with simulta-<br>neous duplex scanning (A6R-A3, capacity:<br>270 sheet A4, paper weight 35-220 g/m <sup>2</sup> ) |
| <b>Platen cover</b>    | Platen cover type E (if document processor<br>is not installed)   |
| <b>Finisher</b>        | DF-7120 (capacity: 1,000 sheet A4, stapling<br>max 50 sheet A4), DF-791 (capacity: 3,000<br>sheet A4, stapling max 65 sheet A4), PH-7C<br>hole punch unit for DF-7120/DF-791, MT-<br>730 (B) multi tray for DF-791  |
| <b>Paper feed</b>      | PF-791 (2 x 500 sheet universal cassettes<br>[A5R-A3]), PF-810 (2 x 1,500 sheet large<br>capacity cassette [A4])  |
| <b>Other options</b>   | Scan extension kit (A), Data security kit (E),<br>Internet fax kit (A), Card authentication kit<br>(B), Keyboard holder (10), UG-33 ThinPrint®<br>kit, UG-34 Emulation option kit, IB-50<br>Gigabit Ethernet card, IB-51 WLAN card,<br>IB-35 WLAN card, DT-730 (B) Document<br>tray, NK-7100 Numeric Keyboard (10<br>keys), HD-12 (320 GB HDD**for the 3262i),<br>cabinet no. 70  |

\*Depending on operating status.

\*\*For copy, print, scan, fax.

\*\*\*optional

Specifications subject to change without notice. Image shows  
machine with optional accessories.

The 3262i and the 4062i are manufactured in accordance with  
the requirements of the Energy Star Program

TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document work-flows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.

[www.triumph-adler.fr/en](http://www.triumph-adler.fr/en)

