

Environmental Data Sheet

TASKalfa 352ci

Environmental Management	This device is manufactured in production facilities that work with an environmental management system in accordance with ISO 14001.
Power Consumption Heat Emission	Maximum (incl. options): 1346 W 4846 kJ/h Printing: 521 W 1876 kJ/h Ready: 84 W 302 kJ/h Sleep-mode: 0.6 W 2.2 kJ/h Off-mode: 0.2 W 0.7 kJ/h
Typical Power Consumption (TEC) (determined according to ENERGY STAR 2.0)	1.622 kWh/week
Installation Notes	The unit should be placed in a way, that there is adequately space for operation and maintenance on both sides, as well as in front and behind the system. Provide adequate ventilation. Do not set up the unit in dusty rooms, and protect against ammonia vapors. Please follow the instructions in the user manual.
Humidity	10% – 80%
Room Temperature	10.0°C – 32.5°C
Noise Emission (according to ISO 7779)	Surface sound pressure level (measurement in 1m distance, average of single measurements) Operation: monochrome: 50.3 dB(A) L_{pA} colour: 50.4 dB(A) L_{pA} Ready: 29.6 dB(A) L_{pA} Operator position Operation: monochrome: 55.9 dB(A) L_{pA} colour: 56.1 dB(A) L_{pA} Ready: 31.6 dB(A) L_{pA} According to DE-UZ 205 Operation: monochrome: 67.1 dB(A) $L_{WA,d}$ colour: 67.2 dB(A) $L_{WA,d}$ Ready: 43,4 dB(A) L_{WA}
Light Source	Exposure drum: Laser
Emission	According to DE-UZ 205 TVOC (Operation): colour mode: 3.49 mg/h TVOC (Ready): colour mode: 0.077 mg/h Benzene: colour mode: < limit of detection Styrene: colour mode: 0.38 mg/h Ozone: colour mode: < limit of detection Dust: colour mode: 0.29 mg/h

effective 12/2019 – Errors and omissions excepted